



AS Rubber & Plastics Limited

Elwell Street, West Bromwich B70 0DN

Tel: 0121 520 5782 Fax: 0121 520 3515

Website: www.asrubber.com Email: info@asrubber.com

Specification Sheet

AS810 – PVC FOAM – 100-120 KGS/M³ SLOW RECOVERY

COLOUR:	WHITE/ BLACK
DENSITY:	100-120KGS/M3
WIDTH:	1000mm - 1400mm
THICKNESS (mm)	2,3,4,5,6,8,10,12,15,18,20
ROLL LENGTH:	From 25 to 130 Metres according to the thickness.

<u>Properties</u>	<u>Unit</u>	<u>Value</u>	<u>Test Method</u>
Density	kgs/m3	100-125	
Tensile Strength	kpa	>150	DIN 53571
Elongation at Break	%	>120	DIN 53571
Tear Strength	N/mm	>80	DIN 53515
Compression Set	%	<45	DIN 53572
Compression Deflection	kpa	0s 12-33 60s 4-16	ASTM 1667
Shore 00 Hardness		20-40	
Waterabsorption	%	>30	
Compression Waterseal		>30%	U-TEST

Flammability	mm/min	<100 >6mm	FMVSS302
Temperature Range	deg C	-30/+60	