



AS Rubber & Plastics Limited

Elwell Street, West Bromwich B70 0DN

Tel: 0121 520 5782 Fax: 0121 520 3515

Website: www.asrubber.com Email: info@asrubber.com

Specification Sheet

AS.812 – P.V.C. FOAM - 120KGS/M³

COLOUR:	WHITE/ BLACK
DENSITY:	100-120KGS/M ³
WIDTH:	1000mm - 1400mm
THICKNESS (mm)	2,3,4,5,6,8,10,12,15,18,20
ROLL LENGTH:	From 25 to 130 Metres according to the thickness.

<u>Properties</u>	<u>Unit</u>	<u>Value</u>	<u>Test Method</u>
Density	kgs/m ³	100-125	
Tensile Strength	kpa	>150	DIN 53571
Elongation at Break	%	>120	DIN 53571
Tear Strength	N/mm	>0.7	DIN 53515
Compression Set	%	<20	DIN 53572
Compression Deflection	kpa	0s 2-12 60s 2-7	ASTM 1667
Shore 00 Hardness		7-30	
Waterabsorption	%	-	

Compression Waterseal		>90%	U-TEST
Flammability	mm/min	<100 >6mm	FMVSS302
Temperature Range	deg C	-30/+60	