



# AS Rubber & Plastics Limited

Elwell Street, West Bromwich B70 0DN

Tel: 0121 520 5782 Fax: 0121 520 3515

Website: [www.asrubber.com](http://www.asrubber.com) Email: [info@asrubber.com](mailto:info@asrubber.com)

## Material Safety Data Sheet

### AS901 – Solid Commercial Rubber

#### GENERAL INFORMATION

Rubber products supplied will contain

- a) Rubber Hydrocarbon base which may be Natural rubber, Styrene/Butadiene rubber, Polychloroprene rubber (Neoprene), Acrylonitrile-Butadiene rubber (Nitrile), Isobutylene/Isoprene rubber (Butyl), Hypalon Silicone, Viton or Ethylene-Propylene rubber (EDPM).
- b) Rubber fillers which may be either carbon black or inorganic: e.g. calcium carbonate, clay, etc..
- c) Rubber process oils and processing aids.
- d) Antioxidant/Antioxonant protective agents
- e) Cure activating agents (accelerators) and curative (normally sulphur)

Generally, these materials are recognised and established rubber ingredients exhibiting no health hazard when commanded and included into the vulcanised rubber. Where, for technical reasons, a potentially hazardous material must be included into a recipe, then special and particular instructions for handling will be provided to customers. However, such instances would be exceptional and should be regarded as exhibiting little hazard to health.

- f) Anti-tack agents are used to prevent sheets of rubber adhering together, and can be one of three types

1) Dry Powder – is dusted with an anti-tack agent. This may be regarded as a nuisance dust with an OEL of 10mg/m<sup>3</sup> total dust and is non-toxic.

2) Wet Film

3) Polyethylene Film – will burn in air and continue to burn and melt after ignition source is removed.

Water or Carbon Dioxide is the recommended spray extinguishing media.

Static electricity can be generated when polythene film is peeled from the rubber surface, and if discharged to earth via the human body, could cause a mild electric shock or spark. Flammable solvents or dusts must, therefore, be kept clear of the area where the peeling operation takes place.

The operator should also wear anti-static footwear.

## **HEALTH INFORMATION & PROTECTION**

In common with most rubber products, rubber materials will burn once ignited, with the evolution of dense smoke. As with all organic matter, the combustion products will include toxic gasses (eg. Carbon Monoxide). Therefore, inhalation of the fumes must be avoided.

Buffering operations can cause the formation of rubber accumulations, which are an explosion and fire hazard.

**Handling:** - Certain individuals may suffer dramatic reaction and when handling – in particular hot materials – are advised to wear gloves.

**Eye Protection:** - Safety glasses during machining/buffing operations.

**Respiratory Protection:** -Should not be necessary.

**Clothing:** - Overalls recommended

**Ventilation:** -Storage areas and areas where buffing operations are undertaken should be well ventilated and consideration given to LEV.

**Hygiene:** - Good personal hygiene is essential. It is always advised to avoid drinking and smoking in work areas.

## **FIRE AND EXPLOSION HAZARD DATA**

**Flash Point:** - Combustible if in contact with flame.

**Extinguishing Media:** - Water, Foam, Sand or Earth.

**Special Procedures:** - Breathing apparatus should be available for use if circumstances dictate.

**Unusual Hazards:** - Will burn with emission of dense black smoke.  
Combustion products will include toxic gases such as Carbon Monoxide, Carbon Dioxide and Oxides Of Nitrogen.  
High temperatures may cause emission of oxidation products.  
Halogen-containing material may emit Hydrogen Halides eg, Hydrogen Chloride.

**Reactivity:** - Stable  
Avoid strong oxidising agents.  
Keep away from excessive and prolonged heat.  
Do not expose to naked flame

## **FIRST AID**

**Eye Contact:** - Treat as a foreign body. Irrigate with clean water.  
Fumes from rubber exposed to excessive heat may cause irritation.

**Skin Contact:** - Short term exposure not considered hazardous.  
Wash hands after use.

**Inhalation:** - No Hazard at ambient temperature.

**Ingestion:** -Seek medical help.

## **SPILLAGES AND DISPOSAL**

Sweep or pick up.

May be disposed of at approved tips or incinerated under approved conditions in accordance with the requirements of the local Waste Disposal Authority.